

Declaration of Performance No. DOP_B0048

ABLOY LOCK CASE

Manufacturer:

Abloy Oy
Björkboda factory
Konttorintie 2
FI-25860 Björkboda
FINLAND

ABLOY® 4203**Intended use of the construction product:**

Lock for interior fire door.

System or systems of
assessment and verification
of constancy of
performance of the
construction product:
AVCP 1

**NOTIFIED PRODUCT
CERTIFICATION BODY:**

VTT Expert Services Ltd
ID No. 0809
PO Box 1001
FI-02044 VTT
FINLAND

Notified product certification
body performed the
determination of the product
type on the basis of type
testing (including sampling),
initial inspection of the
manufacturing plant and of
the factory production
control and continuous
surveillance, assessment
and evaluation of factory
production control and
issued the certificate of
constancy of performance
of the product.

No. 0809-CPD-0701

Category of use	3	High chance of misuse, e.g. doors in public buildings	EN12209:2003 Building hardware - Mechanically operated locks, latches and locking plates
Durability and load on latch bolt	X	200 000 test cycles	
Door mass and closing force	7	Up to 100 kg door mass	
Suitability for use on fire/smoke doors	1	Suitable for use on fire/smoke resisting door	
Safety	0	No safety requirement	
Corrosion resistance and temperature	F	High corrosion resistance, from -20 °C to +80 °C	
Security and drill resistance	-	Not applicable	
Field of door application	H	Mortice lock for hinged door	
Type of key operation and locking	0	Not applicable	
Type of spindle operation	2	Unsprung lever handle	
Key identification	0	No requirements	

Björkboda, 28-June-2013


Jouni Haapaniemi, Vice President
Abloy Oy, Lock Cases