


# VALVE LOCKOUT

## GATE VALVE LOCKOUT

- Virtually indestructible valve covers.
- Once locked, they rotate freely around the hand wheel & prevent the valve wheel from being turned.
- The strong polyurethane plastics make them resistant to cracking and abrasion.
- They are resistant to extreme weather and temperature conditions.
- Available in 5 sizes ( Red colour ) Other colours are available on request (minimum quantity applicable).
- Padlock holes are available in each gate valve lockout device.
- Withstands temperatures from - 20°F to 200°F.
- Unique knockout center accommodates OS & Y or "rising stem" valves.
- Hasps and padlocks can be used to lock these lockouts.



Make a cutout with sharp blade for accommodating rising spindle stem valves



### Dimension

Model	ES - 02 - GVL	ES - 04 - GVL	ES - 06 - GVL	ES - 08 - GVL	ES - 10 - GVL
Size	25 - 63.5 mm	63.5 - 127 mm	127 - 165 mm	165 - 254 mm	254 - 355 mm
Inside Dia (A)	70 mm	130 mm	170 mm	257 mm	355 mm
Inside Depth (B)	32 mm	34 mm	41 mm	50 mm	63 mm
Outside Dia (C)	76 mm	140 mm	177 mm	267 mm	368 mm
Outside Height (D)	38 mm	44 mm	50 mm	63 mm	74 mm

Other available colours



YELLOW



GREEN



BLUE

\* Minimum quantity 100 Nos.

MODEL	GVL : Gate Valve Lockout
ES - 02 - GVL	Fits on handle wheel dia from 25 to 63.5 mm (1" - 2½" inch)
ES - 04 - GVL	Fits on handle wheel dia from 63.5 to 127 mm (2½" - 5" inch)
ES - 06 - GVL	Fits on handle wheel dia from 127 to 165 mm (5" - 6½" inch)
ES - 08 - GVL	Fits on handle wheel dia from 165 to 254 mm (6½" - 10" inch)
ES - 10 - GVL	Fits on handle wheel dia from 254 to 355 mm (10" - 13" inch)

