

No.: DoP-131.03

1. Unique identification code of the product-type:

Electromechanical striking plate (Electric strike) according to EN 14846:2008

Electric strike model 131 in all variants

2. Intended use/s:

Electric strike for use on fire and smoke protection doors according to EN 14846:2008

3. Manufacturer:

ASSA ABLOY
Sicherheitstechnik GmbH
Bildstockstraße 20
72458 Albstadt
GERMANY

4. Authorised representative:

N/A

5. System/s of AVCP:

System 1 according to EN 14846:2008

6.a Harmonised standard:

Notified body	Harmonized standard	Certificate of Constancy of performance
MPA NRW, Marsbruchstraße 186; D-44287 Dortmund, identifier:0432	EN 14846:2008	0432-CPR-00007-04

6.b European Assessment Document:

N/A

7. Declared performance/s:

Declared performance according to EN 14846:2008

Essential characteristics	Requirement clauses EN 14846:2008	Product performance
Self-closing ability	5.4. Door mass and closing force, Annex A Door mass Closing force	passed, (see classification key (3*) with door (mass 300 kg)) passed, (see classification key (3))
Durability of self-closing action	5.3. Durability of latch action	passed, (see classification key (2*))
Ability to maintain door in closed position, and not contribute to the spread of fire	5.5 Fire test according to EN 1634-1	passed, (see classification key (4*))

Classification key according to EN 14846:2008

Position	1	2	3	4	5	6	7	8	9	
Section	4.3	4.4	4.5	4.6	4.7	4.8	4.9	4.10	4.11	
Class	3	X	6	C	-	0	0	0	1	AC
Class	3	X	6	C	-	0	0	1	1	AC
Class	3	C	6	C	-	0	0	0	1	DC
Class	3	C	6	C	-	0	0	1	1	DC

Pos.	Characteristics	Class – Performance							
1	Category of use	3	For use by the public where there is little incentive to exercise for care an where there is a high chance of misuse						
2	Durability and load on latch bolt		test cycles			load on latch bolt [N]			
		C X	200.000 200.000			0 120			
3	Door mass and closing force		door mass [kg]			closing force [N]			
		6	≥ 200 (≤300 kg)			25			
4	Suitability for use on fire and smoke doors		use						
		C	with a classification time of 30 minutes						
5	Safety	-	No safety requirement						
6	Environmental conditions		corrosion resistance [h]		temperature [°C]		humidity		
	Corrosion resistance in accordance with EN 1670:2007 Resistance to a range of temperatures in accordance with EN 60068-2-1:2007 and EN 60068-2-2:2007 Resistance to cyclic humidity in accordance with EN 60068-2-30:2005	0	none		none		none		
7	Security (burglary resistance)	0	no security effect						
8	Security- electrical function	0 1	No requirements Status indicator according to 5.9 EN 14846:2008						
9	Security- electrical manipulation		Protection against effect of			Resistance to	Resistance to (EN 61000-4-2)		
			Voltage drop	Cutting cables	Wire manipulation	Electromagnetic manipulation	Electrostatic discharge	Electrostatic manipulation	
		1	-	-	-	-	Level 2	-	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

N/A

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stefan Fischbach, Managing Director

At Albstadt on 15.03.2021

A handwritten signature in black ink, appearing to read 'Stefan Fischbach', with a long, sweeping underline.

ASSA ABLOY
Sicherheitstechnik GmbH
Bildstockstraße 20
72458 Albstadt
GERMANY
Tel. +497431 123-0
Fax +497431 123-240
www.assaabloyopeningsolutions.de

ASSA ABLOY is the
global leader in
access solutions.
Every day we help
people feel safe,
secure and
experience a more
open world.
www.assaabloy.com